

# SF-SW0908HIPOE-120

Safire Switch Hi-PoE

8 PoE port(s) + 1 Up-link port(s)

Port speed 10/100Mbps

6 PoE+ Ports 30W + 2 Hi-PoE Ports

60W

Total PoE power of 120W

PoE Watchdog / Auto PoE Extended

Up to 250m



Desktop Switch

9 mbps ports RJ45 10/100

6 PoE+ ports 30W 802.3af/at + 2 Hi-PoE ports 60W 802.3bt

Supports PoE power supply up to 120W in total for all ports

AI Watchdog

Auto PoE Extended up to 250m 10Mbps

# Specifications

<b>Interface</b>	8 RJ45 PoE port(s) + 1 Up-link port(s)
<b>Port speed RJ45</b>	8x 10/100Mbps - 1x 10/100Mbps
<b>PoE features</b>	Up to 120W in total for all ports Ports 1-6 PoE+ Up to 30W 802.3af/at Port 7-8 Hi-PoE Up to 60W 802.3af/at/bt Auto PoE Extended 250m a10Mbps
<b>Transmission distance</b>	There is no need to manually configure the Extended PoE function, the switch automatically detects the distance of the cable and the distance of the cable to the switch
<b>Bandwidth</b>	1.8Gbps
<b>MAC Table</b>	2K
<b>Latency</b>	10 to 100MBps < 16?s (using 64 packet size byte)
<b>AI PoE</b>	PoE Watchdog Ports 1-8 - Automatic restart of the power supply to a PoE port when a possible failure is detected.
<b>Power</b>	AC Front Socket 90-240 V
<b>Protections</b>	6KV against Rays 8KV ESD Protection
<b>Operating temperature</b>	-30° C - 60° C
<b>Dimensions</b>	187 (D) x 43 (H) x 139 (W) mm
<b>Weight</b>	1Kg