

SF-SWI2624HIPOE-GF-AC-390-DIN

Safire Industrial Switch Industrial AC

Power 90~264V

24 Gigabit + 2 Gigabit SFP ports

18 PoE+ Ports 30W + 6 Hi-PoE Ports

60W

PoE Watchdog

Up to 390W Total PoE Power

DIN rail installation



IP40 Industrial Switch

AC power supply

24 RJ45 Gigabit 10/100/1000 ports [%VAR%] Mbps

18 PoE+ ports 30W 802.3af/at + 6 Hi-PoE ports 60W 802.3bt

2 SFP Gigabit ports

Supports PoE power supply up to 390W in total for all ports

AI Watchdog

Extended temperature range -40°C to 70°C

DIN-rail installation

Specifications

Interfaces	24 ports RJ45 + 2 SFP
Port speed RJ45	18x RJ45 Gigabit PoE 10/100/1000Mbps 2 SFP Gigabit 10/100/1000Mbps
PoE features	Up to 390W in total for all ports Ports 1-6/9-14/17-22 PoE+ Up to 30W 802.3af/at Ports 7-8/15-16/23-24 Hi-PoE Up to 60W 802.3af/at/bt
Transmission distance	130 meters
Bandwidth	52Gbps
Reshipment Rate	38,68Mbps
MAC Table	8K
Latency	10 to 100MBps < 16?s (using 64 packet size byte)
AI PoE	PoE Watchdog Ports 1~24 - Automatic restart of the power supply to a PoE port when a possible failure is detected.
Power	AC 90~264V
Protections	6KV against Rays 8KV ESD Protection IP40
Operating temperature	-40° C - 70° C
Dimensions	145 x 110 x 160mm
Weight	1,86 Kg